



Division of Soft Play Europe S.A.
Avenue du Progrès, 19
BE - 4432 ALLEUR
BELGIUM

EZ Dock General Specifications

1. Float and Deck Design Standard

- 1.1 The individual dock section shall consist of decking surface and the float structure, which are to be constructed as a single, integrated component. Each section shall provide for the support of the dead load plus a specified live load of 62.5 pounds per square foot (lb/ft²). This shall be accomplished without the use of foam for either structural integrity or floatation. The dock sections shall be manufactured by a rotational molding process and each dock section shall be subject to the specific parameters of the particular model.
- 1.2 The individual dock section shall consist of a specified number of interior, air filler pylons. These pylons shall provide for flotation in the event of a breach of an exterior wall of the dock section; as well as the structural support for the deck portion of the float. Each pylon shall support the dead load plus a live load of 55 pounds (lb) The volume of each pylon shall be no less that 1540 cubic inches (in³).
- 1.3 The individual dock sections shall be constructed of the following materials with the following general properties:
 - a. 100% Virgin Linear Low Density Polyethylene (LLDPE), as that supplied by Mobile Polymers U. S., Inc. as NRP-135.
 - b. An ultraviolet inhibitor (UV-8).
 - c. A beige colorant, supplied by Teknor Color Company as DC-73118 at usage rate of 128 grams (g) per 100 pounds (lb) of LLDPE.
 - d. The density of the section shall be approximately .940 grams per cubic centimeter (g/cm³), per ASTM 1505.
 - e. The dock section shall have a brittleness temperature equal to, or less than, -130° Fahrenheit (F), per ASTM D-746.
- 1.4 The properties of the exterior wall of the dock sections shall be as follows:
 - a. The mean wall thickness shall be no less that .310 inches (in).
 - b. The wall thickness shall be no less than 0.290 inches (in) at any particular point.

Sales & Customer Service +32 (0) 4 384 05 61
Marketing +32 (0) 4 384 05 82
Purchasing +32 (0) 4 384 05 80
Accounting +32 (0) 4 384 05 70
Fax +32 (0) 4 384 05 99
E-mail info@ezdockeurope.com
Website www.ezdockeurope.com

R.P.M. 0444803594 Liège
T.V.A. BE 444.803.594

Fortis 250-0167217-74
ING 350-0241181-61

Make It Easy!



Division of Soft Play Europe S.A.

Avenue du Progrès, 19
BE - 4432 ALLEUR
BELGIUM

- c. The walls of the dock sections shall resist a punching shear of no less than 1900 pounds per square inch (lb/in^2), per ASTM D-732, as well as having the capability of resisting a minimum impact of no less than 110 foot pounds (ft-lb), per ASTM D-3029.
- d. The tensile strength @ break shall be no less than 24000 pounds per square inch (lb/in^2), per ASTM D-638.

1.5 The decking surface shall be composed of a textured surface with a grid pattern for added adhesion during dry conditions. The deck shall have an approximate coefficient of friction equal to 0.64 during dry conditions. The decking surface shall also provide for an increased adhesion of approximately 25% when wet, or a coefficient of friction that is approximately equal to 0.85. Drainage of the decking surface shall be accomplished through the use of troughs, which shall have a width of no more than 0.5 inches (in) and a depth of no more than 0.5 inches (in). The drainage troughs shall extend over the width of the dock and shall be positioned at intervals of no less than 4.5 inches (in) and no greater than 6.5 inches (in) over the entire length of the deck.

1.6. The properties of the decking surface shall be as follows:

- a. The mean deck thickness shall be no less than 0.315 inches (in).
- b. The deck thickness shall be no less than 0.290 inches (in) at any particular point.
- c. The deck shall resist a punching shear which is no less than 1900 pounds per square inch (lb/in^2), per ASTM D-732.
- d. The deck shall resist a minimum impact of no less than 120 foot pounds (ft-lb) near the center, or at the point where the deck is thinnest, per ASTM D-3029.
- e. The deck shall resist a minimum impact of no less than 150 foot pounds (ft-lb) within 16 inches (in) of the outside of the dock, per ASTM D-3029.

2. Floating Dock Structure

2.1 The dock structure, as a whole, shall consist of the individual sections, which are to be coupled together in the specific configuration desired by the purchaser. Any material used in the dock structure shall provide for resistance to rust, corrosion, and the effects of any fuel or gasoline.

Sales & Customer Service +32 (0) 4 384 05 61
Marketing +32 (0) 4 384 05 82
Purchasing +32 (0) 4 384 05 80
Accounting +32 (0) 4 384 05 70
Fax +32 (0) 4 384 05 99
E-mail info@ezdockeurope.com
Website www.ezdockeurope.com

R.P.M. 0444803594 Liège
T.V.A. BE 444.803.594

Fortis 250-0167217-74
ING 350-0241181-61

Make It Easy!



Division of Soft Play Europe S.A.
Avenue du Progrès, 19
BE - 4432 ALLEUR
BELGIUM

2.2 A drawing of the final configuration, including any accessories, shall be supplied for the purchaser if desired.

2.3 The dock structure shall act as one unit when assembled, so that wave and/or wind action shall produce a minimum amount of motion. The structure shall be secured with either piles, spuds, bottom anchors, or stiff arms. The securing shall allow the structure to rise and fall freely with any water level changes and allow the structure to span waves from crest to crest, while providing a stable walking surface.

3. Connections of Dock Sections

3.1 Each dock section shall have female-type pockets spaced symmetrically along the top and bottom edges, around the entire perimeter of the dock section. These pockets shall be spaced at 19.5 inch (in) intervals, center line to center line, from each other.

3.2 The female-type pockets shall accept a male-type coupler which shall be secured into the female pocket with the use of a 0.5 inch (in) X 13 inch (in) coupler bolt and nut.

3.3 The purpose of such connections is to provide for simple assembly and disassembly, as well as providing for the securing of one section to another. The connection will also provide for the ability to attach EZ Dock accessories to the dock sections.

3.4 Each connection point shall allow for some slippage in the event that an extreme stress is applied. This slippage will allow for disconnection without causing damage either to the male-type couplers or the female-type pockets.

3.5 The dock sections shall be connected at increments of 19.5 inches (in), in relation to each other. These connections may be made from any one side of any dock section to any other side of another dock section. These connections may also be used to connect dock sections of differing dimensions and shall provide for ease of assembly, whether the sections are to be assembled on land or in the water.

3.6 The male-type coupler shall be constructed of no less than 90% post/pre-consumer recycled tire rubber.

3.7 Each male-type coupler shall withstand a pullout force of no less than 2500 pounds (lb) before failure of coupler occurs.

Sales & Customer Service +32 (0) 4 384 05 61
Marketing +32 (0) 4 384 05 82
Purchasing +32 (0) 4 384 05 80
Accounting +32 (0) 4 384 05 70
Fax +32 (0) 4 384 05 99
E-mail info@ezdockeurope.com
Website www.ezdockeurope.com

R.P.M. 0444803594 Liège
T.V.A. BE 444.803.594

Fortis 250-0167217-74
ING 350-0241181-61

Make It Easy!



Division of Soft Play Europe S.A.

Avenue du Progrès, 19
BE - 4432 ALLEUR
BELGIUM

3.8 Each of the female connection pockets shall provide for a pullout strength of no less than 3500 pounds (lb), before damage is caused to the dock section.

3.9 The accessories shall be connected to the dock system through the use of the female-type pocket and a male-type half-coupler. The male-type half-coupler shall have a 3.625 inch "T" -bolet embedded within it. The male-type half-coupler shall withstand a pullout force of no less that 3000 pounds (lb) before failure occurs.

4. Cleats

4.1 The tie up cleats shall be constructed of nylon 6,6 and shall have a length of 8-1/16 inches (in) and a height of 1-1/2 inches (in). The cleats shall be connected to the dock sections by two 5/16 inch (in) stainless steel bolts that are threaded into two stainless steel "T" nuts which are molded directly into the dock section. Each of the "T" nuts shall provide for a pull out force of no less that 2000 pounds (lb), so that the cleat may withstand a force of no less that 4000 pounds (lb).

4.2 T "T" nuts shall be molded in the dock section in sets of two, with the distance between the two "T" nuts being 2-1/4 inches (in).

4.3 There shall be three sets of "T" nuts placed along the length of each side of the dock section. The sets of "T" nuts shall be placed at equal distances between the first and second pockets, between the third and fourth pockets, and between the fifth and sixth pockets, along both sides of the dock section.

4.4 There shall be one set of "T" nuts at one end of the 40 inch (in) wide dock section placed at equal distances between the two pockets.

4.5 There shall be two sets of "T" nuts at one end of the 60 inch (in) wide dock section placed at equal distances between the three pockets.

4.6 There shall be two sets of "T" nuts at both ends of the 80 inch (in) wide dock section. These "T" nuts shall be places at equal distance between the first and second pockets, and between the third and fourth pockets.

5. Anchorage

5.1 The dock system shall be designed to allow for the use of piling of various sizes, spud pipes, cables, or chains attached to a bottom anchor, or stiff-arm attachments for anchorage. Calculations can be supplied at purchaser's request to support designed anchorage.

Sales & Customer Service +32 (0) 4 384 05 61
Marketing +32 (0) 4 384 05 82
Purchasing +32 (0) 4 384 05 80
Accounting +32 (0) 4 384 05 70
Fax +32 (0) 4 384 05 99
E-mail info@ezdockeurope.com
Website www.ezdockeurope.com

R.P.M. 0444803594 Liège
T.V.A. BE 444.803.594

Fortis 250-0167217-74
ING 350-0241181-61

Make It Easy!



Division of Soft Play Europe S.A.
Avenue du Progrès, 19
BE - 4432 ALLEUR
BELGIUM

6. Railing Attachment

6.1 The dock structure shall have the ability to accept railing which is constructed to meet the standards established by both the States Organization for Boating Access (SOBA) and the National Uniform Building Code (NUBC). The railing shall be constructed of 1.5 inch (in) O. D., 14 gauge steel tubing. The steel tubing shall be finished either by a 0.003 inch (in) Hot-Dip Galvanizing or by powder coating painting process.

7. Designing for Layout

7.1 The dock system, anchorage, and connections shall be designed according to the recommendations of the American Society of Civil Engineers Manual and Report on Engineering Practice Number 50, "Planning and Design Guidelines for Small Craft Harbors", the revised edition.

8. Main Docks

8.1 The main docks are the walkways which are subjected to the most amount of traffic. These should be designed to provide for comfortable and easy walking widths. Do to the design of the dock system not allowing for such things as pumps, power supplies, boxes, etc. to be attached to them, the overall width of the 60 inch (in) wide dock or 80 inch (in) wide dock is sufficient to accommodate most of the amount of pedestrian traffic which may be required.

9. Fingers

9.1 The finger widths should be designed so as to allow for safe and comfortable walking widths. Since the dock system is not generally designed to accommodate boats that are over 30 feet (ft) in length, a 40 inch (in) wide dock is sufficient to provide for finger stability as well as pedestrian safety for finger lengths up to 20 feet (ft) long. If the length of the finger exceeds 20 feet (ft) long, the 60 inch (in) wide docks should be strongly considered.

10. Wind Exposure

10.1 Boat Profile Height – According to the American Society of Civil Engineers (ASCE) manual published in 1969, for the average height profile compared to the length of the boat, the following will apply.

Sales & Customer Service +32 (0) 4 384 05 61
Marketing +32 (0) 4 384 05 82
Purchasing +32 (0) 4 384 05 80
Accounting +32 (0) 4 384 05 70
Fax +32 (0) 4 384 05 99
E-mail info@ezdockeurope.com
Website www.ezdockeurope.com

R.P.M. 0444803594 Liège
T.V.A. BE 444.803.594

Fortis 250-0167217-74
ING 350-0241181-61

Make It Easy!



Division of Soft Play Europe S.A.

Avenue du Progrès, 19
BE - 4432 ALLEUR
BELGIUM

- a. For a 10 foot (ft) long boat.
 1. ASCE average height is 3 feet (ft).
 2. For future considerations, will assume average heights up to 6 feet (ft).
- b. For a 20 foot (ft) long boat.
 1. ASCE average height is 3.5 feet (ft).
 2. For future considerations, will assume average heights up to 7 feet (ft).
- c. For a 25 foot (ft) long boat.
 1. ASCE average height is 3.6 feet (ft).
 2. For future considerations, will assume average heights up to 7.2 feet (ft).
- d. For all calculations done using the average boat profile heights, it will be considered that 100% of the boats using the dock will be twice the ASCE average profile.

10.2 Maximum Wind Exposure – From studies of maximum wind exposure, it is shown that the forces caused by the maximum wind exposure comes from an angle to the boat, instead of directly to the side or to the front of the boat. Due to the non-feasibility of designing a dock system to handle a maximum tornado wind gust, it is suggested that a reasonable wind speed should be chosen. According to the design standards set up by the Army Corps of Engineers, the dock system should be designed to withstand wind speeds of up to 77 miles per hour (mph) or 15 pounds per square foot (lb/ft²).

10.3 Hidden Boats – It is a common practice to use load factors of 10% to 15% for each hidden boat affected by wind force. That is, every boat that is shielded by another boat, either in front of, or on the side of, will have a decrease in the amount of force which is applied to that boat due to the affect of the shielding boat. The use of a force factor of 15% per hidden boat shall be used in any calculations.

10.4 Load From Various Directions – In the designing of the boat dock system, if piles are to be used as the means of support, it is necessary to take into account the force being applied in the direction of the maximum wind exposure only. However, if chains, cables, or deadweights are to be used as the means of support, it would be necessary to take into account the wind exposure from all directions, when designing the dock system.

11. Load Design

11.1 Dead Load

- a. The dead load shall consist of the entire dock system plus any additional attachments to the dock system.
- b. Under dead load conditions, flotation shall provide a minimum of approximately 13.5 inches (in) of freeboard.
- c. The surfaces of adjacent deck surfaces shall have an elevation difference of no more than 0.125 inches (in).

Sales & Customer Service +32 (0) 4 384 05 61
Marketing +32 (0) 4 384 05 82
Purchasing +32 (0) 4 384 05 80
Accounting +32 (0) 4 384 05 70
Fax +32 (0) 4 384 05 99
E-mail info@ezdockeurope.com
Website www.ezdockeurope.com

R.P.M. 0444803594 Liège
T.V.A. BE 444.803.594

Fortis 250-0167217-74
ING 350-0241181-61

Make It Easy!



Division of Soft Play Europe S.A.

Avenue du Progrès,19
BE - 4432 ALLEUR
BELGIUM

- d. The ends of the fingers shall have an elevation of no more than 1 inch (in) above that of the main dock.
- e. The deck surface of each dock section shall not slope more than 0.5 inches (in) over the 10 foot (ft) length of the dock section.
- f. The deck surface of each 80 inch (in) X 10 foot (ft) dock section shall not slope more than 0.35 inches (in) over the width of the dock section.
- g. The deck surface of each 60 inch (in) X 10 foot (ft) dock section shall not slope more than 0.25 inches (in) over the width of the dock.
- h. The deck surface of each 40 inch (in) X 10 foot (ft) dock section shall not slope more than 0.15 inches (in) over the width of the dock section.

11.2 Live Load Due To Vertical Loads

- a. Under dead load conditions plus an additional 20 pounds per square foot (lb/ft²) of uniform live load, flotation shall provide for a minimum of 9 inches (in) of freeboard.
- b. Under dead load conditions, plus an additional 40 pounds per square foot (lb/ft²) of uniform live load, flotation shall provide for a minimum of 5 inches (in) of freeboard.
- c. The dock structure shall support a concentrated vertical load of up to 400 pounds (lb) at any particular point on the surface of the deck. The structure shall accomplish this while maintaining a minimum freeboard of 10.25 inches (in).

11.3 Live Load Due To Horizontal Loads

- a. The dock system shall sustain the loads applied by any current and/or debris which are normal to a particular location.
- b. The dock system shall be capable of sustaining continuous wave action of up to 2 foot and occasional wave action not in excess of 3 feet during storm conditions.
- c. The dock sections shall sustain any loads applied by non-moving ice without damage.
- d. The dock system shall be capable of sustaining the loads applied by mooring boats up to 35 feet in length.

Sales & Customer Service +32 (0) 4 384 05 61
Marketing +32 (0) 4 384 05 82
Purchasing +32 (0) 4 384 05 80
Accounting +32 (0) 4 384 05 70
Fax +32 (0) 4 384 05 99
E-mail info@ezdockeurope.com
Website www.ezdockeurope.com

R.P.M. 0444803594 Liège
T.V.A. BE 444.803.594

Fortis 250-0167217-74
ING 350-0241181-61

Make It Easy!



Division of Soft Play Europe S.A.
Avenue du Progrès, 19
BE - 4432 ALLEUR
BELGIUM

- e. The dock system and anchorage shall be capable of withstanding sustained wind loads of 77 miles per hour (mph), or 15 pounds per square foot (lb/ft²), at 100% boat occupancy, unless otherwise specified.
- f. The dock system shall be capable of withstanding the impact force caused by a 35 foot boat striking the end of a finger at a speed of 2 miles per hour (mph) and at an angle of 10° off center.

Sales & Customer Service +32 (0) 4 384 05 61
Marketing +32 (0) 4 384 05 82
Purchasing +32 (0) 4 384 05 80
Accounting +32 (0) 4 384 05 70
Fax +32 (0) 4 384 05 99
E-mail info@ezdockeurope.com
Website www.ezdockeurope.com

R.P.M. 0444803594 Liège
T.V.A. BE 444.803.594

Fortis 250-0167217-74
ING 350-0241181-61

Make It Easy!